

GSM GATE OPENER

GSM gate opener can be used for gate barrier, shutter, garage door and door opener.

Open gate or door with a free call from your mobile phone!

Remote switching machines with a free call from your mobile phone!



The **GSM** gate opener is a very simple device which can be used for authorised door access, controlling gates, switching of remotes equipment, car parking systems. Actually the GSM gate opener can be used in places which requires turning on/off your system, machines, equipment remotely with a free call from your mobile.

Just dial from authorised user number then the barrier and doors are opened, or the machines are turned on or off by the GSM gate opener. There are no call costs, the GSM system rejects the call then carry's out the on/off action.

Applications the GSM system is suitable for:

Home and garage, Hotels, Warehouses, business, Parking places, Hospitals, other places in need of remote switching application and simple security alarm systems application.

Features include:

No call charges, Secure using caller id for identification unknown callers rejected, Can be opened from anywhere no distance limit, Add or remove users by SMS, No need for remotes to different users, Up to 64 authorised phone numbers can be configured, Two digital inputs for door sensor, motion sensors or other sensors to protect your door and windows, when one is triggered will send SMS to alert you immediately, One output with relay rating 3A/240VAC for connecting the switch of the door or machines, The relay action will return a SMS confirmation to the owner, this function is editable by user, Based on GSM network applied to many applications.

Specifications:

DC Power Supply	Standard adapter DC 12V/1A
Power Consumption	12V input max50mA/ Average 50mA
Frequency range	Dual band 900/1800MHZ or 850/1900MHZ
Sim card	Supporting 3v Sim card
Antenna	50Ω SMA antenna interface
Temp range	-20 to + 60° C
Humidity range	Relative humidity 90% (condensation free)
Relay rating	3A/240VAC
Exterior dimensions	110mm * 90mm * 40mm
Net weight	600G

Standard Package List of GSM System:

GSM gate opener X1

AC to DC adapter X1

User Manual X1

Notes: the package does not include any Sim card

These units will not work on the Optus network.

Optional:

Door sensor, Motion sensor, Temperature sensors and others.