

## PRODUCT INFORMATION

## STANDARD ELECTRO MAGNETIC LOCKS SINGLE/DOUBLE DOOR, SURFACE MOUNT





PART No.		
FEM5700 FEM5700D		FEM5700M FEM5700DM
HOLDING FORCE	Up to 580kg (for single magnetic lock)	
VOLTAGE/ CURRENT	Dual Voltage 12/24VDC, 12VDC=490mA 24VDC=245mA	
APPROVALS	4 hour fire rated to A.S. and B.S. standards, SCEC approved for secure areas (FEM5700M & DM)	
MONITORING	NIL	LP LSS DSS
	Single door series magnet size: L= 268 x W= 73 x D= 40mm	Double door series surface magnet size: L= 535 x W= 73 x D= 40mm
SIZE	Single door series armature plate size: L= 190 x W= 61 x D= 16mm	Double door series armature plate size: L= 190 x W= 61 x D= 16mm x 2 pcs
	Single door series DSS-armature plate size L= 252 x W= 61 x D= 16mm	Double door series DSS-armature plate size: L= 252 x W= 61 x D= 16mm x 2 pcs
WEIGHT	Single door 4.8kg/Double door 9.5kg per set, SCEC approved for secure areas (FEM5700M & DM)	
UNITS PER BOX	Single door 4 per box (19.5kg) Double door 2 per box (19.5kg)	

Common Features

- ◆ Power-off to release door/s
- ♦ No moving parts
- ◆ Built-in varistor (MOV) surge protection
- ◆ Satin anodised aluminum housing & zinc plated electromagnetic lock body
- ◆ Carbon free steel armature plate
- ◆ Lifetime warranty
- ◆ CE/C-Tick
- ◆ SCEC Approved for secure area
- ◆ Anti Tamper Plate (with monitored EML)