

## PRODUCT INFORMATION

## FLECTRO MAGNETIC GATE LOCKS WEATHER RESISTANT







FEM5000G

FEM4700FS

FEM4500FS

PART No.			
FEM5000G		FEM4700FS	FEM4500FS
HOLDING FORCE	Up to 630kg	Up to 380kg	Up to 200kg
VOLTAGE/ CURRENT	Dual Voltage 12/24VDC, 12VDC=480mA 24VDC=240mA	Dual Voltage 12/24VDC, 12VDC=400mA 24VDC=200mA	Dual Voltage 12/24VDC, 12VDC=360mA 24VDC=180mA
MONITORING	LSS	NIL	NIL
SIZE	Magnet size: L= 225 x W= 63 x D= 44mm Armature plate size: L= 190 x W= 61 x D= 16mm	Magnet size: L= 220 x W= 47 x D= 30.5mm Armature plate size: L= 185 x W= 42 x D= 12mm	Magnet size: L= 162 x W= 26 x D= 31mm Armature plate size: L= 130 x W= 30 x D= 8.7mm
WEIGHT	4.75kg	2kg	1kg
UNITS PER BOX	4 per box (19.5kg)	10 per box (21kg)	10 per box (11kg)

Common Features

- ◆ Power-off to release door
- ◆ Unique mounting design
- ◆ Stainless 304 steel body housing
- ◆ Carbon free steel armature plate
- ◆ Built-in varistor (MOV) surge protection
- ♦ Weather resistant
- ◆ Lifetime warranty
- ◆ C €/C-Tick
- ◆ Anti Tamper Plate (with FEM5000G)