

# PRODUCT INFORMATION

## SLIMLINE ELECTRIC DROP BOLT MORTISE MOUNT



DB1260PTO (power to release) DB1260PTL (power to lock)

### PRODUCT DESCRIPTION

DB1260 is designed for narrow frame swing doors, and/or glass door mounting. The drop bolt body depth of 35mm will fit into a 44mm depth door frame. The drop bolt is available in either “power to lock” or “power to release” format. The DB1260 can be wired into any fire/smoke alarm or security access control system.

In “power to release” mode the drop bolt is factory pre-set with a 3 seconds time delay and buzzer on "A" setting (refer to technical information supplied with drop bolt).

PART No.	DB1260PTO (power to release)	DB1260PTL (power to lock)
FUNCTION	Slimline mortise mount drop bolt	
HOLDING FORCE	Up to 300kg	
VOLTAGE/CURRENT	12VDC 1.15A(in-rush) 250mA holding	
APPROVALS	4 hour fire rated to A.S. and B.S. standards	
MONITORING	Door sensor Remote release Bi-coloured LED Audible tone	
SIZE	L= 210 x W= 25 x D= 35mm	
WEIGHT	0.7g	
UNITS PER BOX	10 per box (7.5kg)	

**Mounting installation:** Suitable for mounting on wooden, metal, glass, aluminum and PVC door frames.

### Common Features

- ◆ Internal control circuits protect drop bolt pin from damage
- ◆ Power to lock or power to release (has to be specified)
- ◆ Auto lock function
- ◆ Built-in varistor (MOV) for surge protection
- ◆ Time delay setting at 0/3/6/10 secs
- ◆ 1 year warranty