


GT Series




Colour Video Four Wire Digital Apartment Intercom

16 entries and 500 apartments



Video Apartment Security Intercom

System Configuration



Features

- Hands free or handset apartment stations
- Digital Pan/Tilt and Zoom (GT-1C/GT-2C)
- Modular or all-in-one entrance station
- Up to 500 residences
- Up to 16 common entrance points
- Individual colour video door station per residence (requires GT-2C) .
- Up to 3 colour video sub stations per residence with internal . communication (requires GT-2C)
- Up to 500 access codes for residents
- Concierge or guard station call feature (requires GT-MK)
- Picture memory internal station (requires GT-2C)

Specifications

Power source		24V DC 2/	24V DC 2Amps		
Call-in		Electronic	tone with adj	ustable volume	
Door release		N/O or N/0 4 Amp 24	N/O or N/C dry contact. Contact rating 4 Amp 24V AC or DC		
Wiring		busses. A	2x2 parallel wires, non-polarised for video and audio communication busses. A bus can support up to 25 GT video stations		
Distance					
	Diameter	0.65mm	0.8mm	1.0mm	
	GT-VBC to furthest internal station				
		100m	150m	150m	
	GT-VBC to entrance station				
		50m	100m	300m	

Additional Options

GT-1A

GT-2C

Hands free colour video apartment station with picture memory GT-2CL Hands free colour video apartment station with hearing loop and picture memory GT-2H Hands free colour video sub station GT-2HL Hands free colour video substation with hearing loop GT-1C Hands free colour video apartment station GT-1CL

Hands free colour

video apartment station with hearing loop GT-1ML Handset colour video apartment station with hearing loop in handset GT-HS Optional handset for

Hands free audio apartment station GT-1D Handset audio apartment station with hearing loop in handset GT-DM All-in-one stainless steel colour video door station GT-VA Colour camera module GT-VP Panel GT-DAL Audio module GT-DPL Panel GT-NS Name scroll module GT-NSP Panel GT-10K Keypad panel GF-1P 1 call plate GF-2P 2 call plate GF-3P 3 call plate GF-4P 4 call plate GT-SW

Call switch module

GT-BC Audio bus control GT-BCX Audio bus expander GT-VBC Video bus control GT-VBX Video bus expander GT-4Z 4 way video splitter

GF-2F

2 Module frame GF-3F 3 module frame GT-4F 4 module frame GF-2B Back box GF-3B Back box GT-4B Back box GF-BP Blank panel GT-AC Access control keypad EL-12S Door release GT-RY Light control relay TPS252DC Power supply

Cables

GT-2H/L

GT-1C/L, GT-2C/L,

- 0.5mm ~ 1.2mm (0.9mm recommended)
- PE (polyethylene) insulated cable (KB Wire)
- Solid copper conductor



Your local Aiphone reseller:

